

# TECHNICAL DATA SHEET

**Product:** MASCO SURFACE GRIP  
**Revision Date:** 7/2/2018

## DESCRIPTION

MASCO SURFACE GRIP is a finely ground, slip resistant polymer additive designed specifically for use to improve the slip resistance of film forming sealers. MASCO SURFACE GRIP can be added to all MASCO and most other manufacturer's solvent based film-forming sealers. It is ideal for use on surfaces where water or moisture can accumulate such as garage floors, driveways, patios, walkways, and other smooth surfaces.

## BENEFITS

- Will improve slip-resistance and texture of film-forming sealers
- May be used for exterior or interior applications
- Allows for sprayer, roller and brush applications

## USAGE

- MASCO SURFACE GRIP is compatible with MASCO, solvent-based Cure & Seals, Acrylic Sealer, Hi-Gloss, and Matte Finish sealers.

## MIXING INSTRUCTIONS

Add the desired amount of MASCO SURFACE GRIP to the sealer while mixing. After incorporating the MASCO SURFACE GRIP completely into the sealer, allow it to dwell in the product for at least 30 minutes, and up to 24 hours, before application. If the sealer is not used immediately, it may be necessary to gently re-mix the MASCO SURFACE GRIP into the product before application.

A small test batch and application is recommended when using MASCO SURFACE GRIP in a product for the first time to determine the proper dosage rate for the texture desired.

## APPLICATION

A test area is recommended to verify compatibility with other manufactures film-forming sealers. Mix thoroughly and often prior to and during sealer application. Spray application is recommended but smaller areas may be brushed. Do not re-roll wet areas. Prepare substrate and apply sealer in accordance with the manufactures written instructions.

## COVERAGE

Add 15 oz to 5-gal container of sealer, 3oz to 1-gal container.  
Do not exceed more than 6 oz per gal of sealer.

## LIMITATIONS/PRECAUTIONS

- MASCO Surface Grip will increase the coefficient of

friction and slip resistance of sealers to which it has been added. However, the sealer should not be considered completely non-slip or non-skid.

- When adding MASCO Surface Grip to concrete cure & seals or sealers containing acetone or tertiary butyl acetate (TBAC), the product must be applied immediately after incorporation of MASCO SURFACE GRIP.
- Do not use in penetrating sealers such as silane or siloxane water repellents.
- Do not apply by broadcasting into a wet sealer surface.
- Not recommended for use in water-based products.
- Additional precautions, safety information and first aid are contained in the Safety Data Sheet.

## PACKAGING

15 oz bottle (6 per case)

Storage: 40° F to 85° F

Protect from Freezing.

Shelf Life: 2 years unopened, in protected storage.

DOT Hazard Class: Not DOT Regulated

## TECHNICAL SERVICE

For application procedures of surface conditions not specified above, please contact:

**MASONS SUPPLY COMPANY**  
2637 SE 12th Ave.  
Portland, OR 97202  
(503)234-4321, FAX (503)234-5606  
masco.net

## DISCLAIMER OF WARRANTIES AND LIMITATIONS OF LIABILITY

MASONS SUPPLY CO. (Seller) warrants that if any goods supplied prove defective in workmanship or material, that Seller shall replace them or refund their purchase price. THIS WARRANTY IS MADE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS WHICH ARE HEREBY DISCLAIMED. IT IS UNDERSTOOD AND AGREED THAT BUYER'S SOLE REMEDY, AND THEREFORE SELLER'S LIABILITY, WHETHER IN CONTRACT, TORT, UNDER ANY WARRANTY, IN NEGLIGENCE, OR OTHERWISE SHALL BE LIMITED TO THE RETURN OF THE PURCHASE PRICE PAID BY PURCHASER OR REPLACEMENT OF ANY DEFECTIVE GOOD'S SOLD BY SELLER AND UNDER NO CIRCUMSTANCES SHALL SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES. THE PRICE STATED FOR THE GOODS IS A CONSIDERATION IN LIMITING SELLER'S LIABILITY. Before application, the User shall determine the suitability of the product for his intended use and User assumes all risks and liabilities whatsoever in connection therewith. The terms of this paragraph may not be orally modified. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE FACE HEREOF.